

Unit 11, Gunnels Wood Park, Stevenage, Hertfordshire SG1 2BH Sales@elecro.co.uk | +44 (0) 1438 749474

www.elecro.co.uk



# QUANTUM

Quantum uses new ceramic Nano Crystal technology, a prime focus of the science world today; possessing the power to sterilise sewage into drinking water without the use of chemicals.





# **FEATURES**

- · Photocatalytic TiO2/Mo oxidiser and clarifier
- Combined photocatalytic, hydroxyl radical and UV technology
- Eliminates contaminants, leaving water looking fresh and clean
- · Reduces the need for chemicals in the pool
- Keeps your family safe from dangerous microorganisms such as cryptosporidium, adenoviruses and naegleria fowleri

- Optional smart peristaltic dosing system for chlorine and hydrogen peroxide
- Powerful sterilisation and eliminates the smell of chlorine
- · Average lamp life expectancy: 2 years
- · Equipped with intelligent lamp life indicator
- · Salt and sea water compatible

# **TECHNICAL DRAWINGS**






## PRESSURE DROP

#### PRESSURE DROP PRIMARY CIRCUIT

PRESSURE (BAR)



Q-130 & QP-130

Q-65 & QP-65

# **SPECIFICATIONS**

POWER SUPPLY	100V ~ 240V				
MIN. FLOW RATE	4m³/h				
MAX. FLOW RATE	Single Tube: 14,000 litres per hour; 14 m³/h Double Tube: 28,000 litres per hour; 28 m³/h				
MAX. POOL SIZE	Single Tube: 65,000 litres; 65m³ Double Tube: 130,000 litres; 130m³				
MAX. POWER CONSUMPTION	Single Tube: 64W Double Tube: 128W				
LAMP	Low pressure / high output				
LAMP LIFE	14,000 hours				
DOSING RATE	Exceeds the equivalent of 30mj/cm² at max. flow rate				
INGRESS PROTECTION RATING	IP64				
FREQUENCY	50/60 Hz				
WORKING PRESSURE	3 Bar maximum				
WATER CONNECTIONS	2" / 63mm stepped ABS unions + reducers 1½" / 50mm				
SALT WATER	100% sea water safe				
MOUNTING	Floor or wall mounting				
OXIDISATION PROCESSES	Quantum photocatalytic oxidiser (PCO) & hydroxyl radicals (HO)				

# **MODELS**

100-240V 1-PHASE	MAX. POO VOLUME	Р	RODUCT COD	ES	FEATURES	NET WEIGHT	GROSS WEIGHT	VOLUME
Lamp Output	m³	UK Plug Type G	Euro Plug Type F	USA Plug Type B	FEATORES	kg	kg	m³
55 WATTS	65	Q-65-UK	Q-65-EU	Q-65-USA	Analogue lamp life indicator & reset switch	7.1	9.7	0.11
110 WATTS	130	Q-130-UK	Q-130-EU	Q-130-USA	Analogue lamp life indicator & reset switch	11.6	15.1	0.15
55 WATTS	65	QP-65-UK	QP-65-EU	QP-65-USA	Digital lamp life countdown with intelligent dosing pump	7.4	10.1	0.11
110 WATTS	130	QP-130-UK	QP-130-EU	QP-130-USA	Digital lamp life countdown with intelligent dosing pump	11.9	15.5	0.15

#### PHOTOCATALYTIC OXIDATION

Light

#### By product Harmless H<sub>2</sub>O Photo-catalyst Attacking Harmful Pollutants Titanium Dioxide and Co<sub>2</sub> Oxidizing Hydroxyl Radicals Formed Ultra Violet Destruction

of cells

### **OXIDISATION STRENGTH (EV)**

